

# DRSKABEL

| Specifications                                          |                                     |
|---------------------------------------------------------|-------------------------------------|
| <b>Cross Section</b> : 5x240mm <sup>2</sup> NYY (YVV-R) |                                     |
| <b>Voltage</b> : 0,6/1kV (1,2kV)                        |                                     |
| <b>Diameter</b> : 69,9 (mm)                             | <b>Weight</b> : 15.087 (kg/km)      |
| <b>Conductor DS Resistance Ohm/km (20°C)</b><br>0,0754  |                                     |
| Current Carrying Capacity                               |                                     |
| <i>In Ground at 20 °C</i> <b>473 A</b>                  | <i>In Air at 30 °C</i> <b>445 A</b> |



| Nr. | Construction        | Property           | Net Weight (kg/km) | Detail                   |
|-----|---------------------|--------------------|--------------------|--------------------------|
| 1   | <b>Cu conductor</b> | Stranded copper    | 10667              | 48x2,62mm                |
| 2   | <b>Insulation</b>   | Polyvinly chloride | 1121               | Et Kal: 2,00mm thickness |
| 3   | <b>Filler</b>       | Polyvinly chloride | 2385               | Et Kal: 1,50mm thickness |
| 4   | <b>Outer sheath</b> | Polyvinly chloride | 914                | Et Kal: 2,80mm thickness |